

Rounds

Hot Rolled MBQ - A-36

SIZE	LBS./FT.	LBS./20'
1/4	.167	3.34
5/16	.261	5.22
3/8	.376	7.52
7/16	.511	10.22
1/2	.668	13.36
9/16	.845	16.90
5/8	1.043	20.86
3/4	1.502	30.04
7/8	2.044	40.88
1	2.670	53.40
1 1/8	3.380	67.60
1 1/4	4.172	83.44
1 3/8	5.049	100.98
1 1/2	6.008	120.16
1 3/4	8.180	163.60
2	10.680	213.60
2 1/2	16.690	333.80

Cold Drawn Rounds

C1018, C1045, C1144SR, and Stress Relieved Stock Lengths - 12' & 20'

SIZE	LBS./FT.	LBS./20'	SIZE	LBS./FT.	LBS./20'
1/8	.042	.84	1 5/16	4.600	92.00
3/16	.094	1.88	1 3/8	5.050	101.00
7/32	.128	2.56	1 7/16	5.520	110.40
1/4	.167	3.34	1 1/2	6.010	120.20
5/16	.261	5.22	1 9/16	6.520	130.40
3/8	.376	7.52	1 5/8	7.050	141.00
7/16	.511	10.22	1 11/16	7.600	152.00
1/2	.668	13.36	1 3/4	8.180	163.60
9/16	.845	16.90	1 13/16	8.770	175.40
5/8	1.040	20.80	1 7/8	9.390	187.80
11/16	1.260	25.20	1 15/16	10.020	200.40
3/4	1.500	30.00	2	10.680	213.60
13/16	1.760	35.20	2 1/16	11.360	227.20
7/8	2.040	40.80	2 1/8	12.060	241.20
15/16	2.350	47.00	2 3/16	12.780	255.60
1	2.670	53.40	2 1/4	13.520	270.40
1 1/16	3.020	60.40	2 3/8	15.060	301.20
1 1/8	3.380	67.60	2 7/16	15.870	371.40
1 3/16	3.770	75.40	2 1/2	16.690	333.80
1 1/4	4.170	83.40	2 5/8	18.400	368.00